

ZISA OP4616 Cassette OLT Datasheet

Product Overview

OP4616 is a small capacity and enhancement mode cassette GPON OLT, meeting the requirements of *ITU-T G.984/G.988* and relative standards of *China Telecom/Unicom GPON*, possessing super GPON access capacity, carrier-class reliability and the complete security function. It can satisfy long-distance optical fiber access requirement on account of its excellent management, maintenance and monitoring capability, abundant service features and flexible network mode. OP4616 can be used with NGBNVIEW network management system so as to provide users with the perfect solution.

OP4616 provides 16 downlink GPON port, 4 *GE combo port and 2* 10G SFP+ port. The height is only 1U for easy installation and space saving. OP4616 is suitable for Broadcast *three in one*, video surveillance network, enterprise LAN, Internet of Things, etc.

OP4616



- 1 RU19 inch
- 1+1 power redundancy
- 16* fixed GPON port
- 4*GE COMBO port, 2*10GE SFP+ port
- 1*console port

Product Specification:

Item	OP4616
Switching Capacity	140Gbps
Forwarding Capacity(Ipv4/Ipv6)	104MPPS
Service Port	16*PON port, 4*GE SFP, 4*GE COMBO port, 2*10GE SFP+ port
Redundancy Design	Dual power supply Support AC input, double DC input and AC+DC input
Power Supply	AC: input 90~264V 47/63Hz; DC: input -36V~-72V;
Power Consumption	≤110W
Dimensions (Width x Depth x Height)	440mm×44mm×380mm
Weight (Full-Loaded)	≤3kg

Environmental Requirements	<p>Working temperature: -10°C~55°C</p> <p>Storage temperature: -40°C~70°C</p> <p>Relative humidity: 10%~90%, non-condensing</p>
----------------------------	---------------------------------------------------------------------------------------------------------------------------------

Product Features:

Item		OP4616
PON Features		<p>ITU-TG.984.x standard</p> <p>Maximum 20 Km PON transmission distance</p> <p>access 128 terminals for single fiber PON</p> <p>Uplink and downlink triple churning encrypted function with 128Bits</p> <p>ONU terminal legitimacy certification, report illegal ONU registration</p> <p>DBA algorithm, the particle is 1Kbit/s</p> <p>Standard OMCI management function</p> <p>ONU batch software upgrade, fixed time upgrade, real time upgrade</p> <p>PON port optical power detection</p>
L2 Features	MAC	<p>MAC Black Hole</p> <p>Port MAC Limit</p> <p>64K MAC (packet exchange chip cache 2MB, external cache 720 MB)</p>
	VLAN	<p>4K VLAN entries</p> <p>Port-based/MAC-based/protocol/IP subnet-based QinQ and flexible QinQ (StackedVLAN)</p> <p>VLAN Swap and VLAN Remark</p> <p>PVLAN to realize port isolation and saving public-vlan resources</p> <p>GVRP</p>
	Spanning Tree	<p>STP/RSTP/MSTP</p> <p>Remote loop detecting</p>
	Port	<p>Bi-directional bandwidth control</p> <p>Static link aggregation and LACP(Link Aggregation Control Protocol)</p> <p>Port mirroring</p>
Security Features	User's Security	<p>Anti-ARP-spoofing</p> <p>Anti-ARP-flooding</p> <p>IP Source Guard create IP+VLAN+MAC+Port binding</p> <p>Port Isolation</p> <p>MAC address binding to the port and MAC address filtering</p> <p>IEEE 802.1x and AAA/Radius authentication</p>
	Device Security	<p>Anti-DOS attack(such as ARP, Synflood, Smurf, ICMP attack), ARP</p> <p>detection, worm and Msblaster worm attack</p> <p>SSHv2 Secure Shell</p> <p>SNMP v3 encrypted management</p> <p>Security IP login through Telnet</p>

		Hierarchical management and password protection of users
	Network Security	<p>User-based MAC and ARP traffic examination</p> <p>Restrict ARP traffic of each user and force-out user with abnormal ARP traffic</p> <p>Dynamic ARP table-based binding</p> <p>IP+VLAN+MAC+Port binding</p> <p>L2 to L7 ACL flow filtration mechanism on the 80 bytes of the head of user-defined packet</p> <p>Port-based broadcast/multicast suppression and auto-shutdown risk port</p> <p>URPF to prevent IP address counterfeit and attack</p> <p>DHCP Option82 and PPPoE+ upload user's physical location</p> <p>Plaintext authentication of OSPF, RIPv2 and BGPv4 packets and MD5</p> <p>cryptograph authentication</p>
Service Features	ACL	<p>Standard and extended ACL</p> <p>Time Range ACL</p> <p>Flow classification and flow definition based on source/destination MAC address, VLAN, 802.1p, ToS, DiffServ, source/destination IP(IPv4/IPv6) address, TCP/UDP port number, protocol type, etc</p> <p>packet filtration of L2~L7 deep to 80 bytes of IP packet head</p>
	QoS	<p>Rate-limit to packet sending/receiving speed of port or self-defined flow and provide general flow monitor and two-speed tri-color monitor of self-defined flow</p> <p>Priority remark to port or self-defined flow and provide 802.1P, DSCP priority and Remark</p> <p>CAR(Committed Access Rate), Traffic Shaping and flow statistics</p> <p>Packet mirror and redirection of interface and self-defined flow</p> <p>Super queue scheduler based on port or self-defined flow. Each port/</p> <p>flow supports 8 priority queues and scheduler of SP, WRR and SP+WRR.</p> <p>Congestion avoid mechanism, including Tail-Drop and WRED</p>
	IPv4	<p>ARP Proxy</p> <p>DHCP Relay</p> <p>DHCP Server</p> <p>Static Routing</p> <p>RIPv1/v2</p> <p>OSPFv2</p> <p>BGPv4</p> <p>Equivalent Routing</p> <p>Routing Strategy</p>
	IPv6	<p>ICMPv6</p> <p>ICMPv6 Redirection</p>

		<p>DHCPv6 ACLv6 OSPFv3 RIPng BGP4+ Configured Tunnels ISATAP 6to4 Tunnels Dual stack of IPv6 and IPv4</p>
	Multicast	<p>IGMPv1/v2/v3 IGMPv1/v2/v3 Snooping IGMP Filter MVR and cross VLAN multicast copy IGMP Fast leave IGMP Proxy PIM-SM/PIM-DM/PIM-SSM PIM-SMv6, PIM-DMv6, PIM-SSMv6 MLDv2/MLDv2 Snooping</p>
Reliability	Loop Protection	<p>EAPS and GERP (recover-time <50ms) Loopback-detection</p>
	Link Protection	<p>FlexLink (recover-time <50ms) RSTP/MSTP (recover-time <1s) LACP (recover-time <10ms) BFD</p>
	Device Protection	<p>VRRP host backup 1+1 power hot backup</p>
Maintenance	Network Maintenance	<p>Port real-time, utilization and transmit/receive statistic based on Telnet RFC3176 sFlow analysis LLDP GPON OMCI RFC 3164 BSD syslog Protocol Ping and Traceroute</p>
	Device Management	<p>CLI, Console port, Telnet and WEB SNMPv1/v2/v3 RMON (Remote Monitoring) 1,2,3,9 groups MIB NTP NGBNView network management</p>

Purchase Information:

Product name	Product description
OP4608	8*PON, 4*GE SFP, 4*GE COMBO port, 2*10GE SFP+, double AC/DC power supply
OP4616	16*PON, 4*GE SFP, 4*GE COMBO, 2*10GE SFP+, double AC/DC power supply
NG01PWR180AC	power module for NG01PWR180AC
NG01PWR180DC	power module for NG01PWR180DC

Contact us

ZISA Corporation LIMITED

Mail to : sales@zisacom.com.cn

URL: <http://www.zisacom.com.cn>

Specifications are subject to change without notice.

Copyright © ZISA Corp. All rights reserved.