

A Smarter Way for Your Broadband Life

EchoLife EG8245H, an intelligent routing-type ONT

Smart
service

Smart
interconnection



Smart O&M

○ Device Parameters

Dimensions (HxWxD)	176 mm x 138.5 mm x 28 mm (without an external antenna)
Weight	About 280 g
Operating temperature	0°C to +40°C
Operating humidity	5% RH to 95% RH (non-condensing)
Power adapter input	100 – 240 V AC, 50/60 Hz
System power supply	11 – 14 V DC, 1.5 A
Static power consumption	5.5 W
Maximum power consumption	16.5 W
Ports	2POTS + 4GE + Wi-Fi+ 1USB
Indicators	POWER/PON/LOS/LAN/TEL/USB /WLAN/WPS

○ Interface Parameters

GPON Port	<ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27 dBm • Wavelengths: US 1310 nm, DS 1490 nm • WBF • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA
Ethernet Port	<ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning
POTS Port	<ul style="list-style-type: none"> • Maximum REN: 4 • G.711A/μ, G.729a/b and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol)
USB Port	<ul style="list-style-type: none"> • USB2.0 • FTP-based network storage
WLAN	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n • 2 x 2 MIMO • Antenna gain: 5 dBi • WMM • Multiple SSIDs • WPS • Air interface rate: 2. 4G: 300 Mbit/s

○ Product Function

Smart interconnection

- Smart Wi-Fi coverage
- SIP/H.248 auto-negotiation
- Any port any service
- Parental control
- L2/L3 (IPv4) forwarding: 1G uplink, 2G downlink

Smart service

- Smart Wi-Fi sharing:
Portal/802.1x authentication
SoftGRE-based sharing
- Association of one account with two POTS ports

Smart O&M

- IPTV video quality diagnosis
- Variable-length OMCI messages
- Active/Passive rogue ONT detection and isolation
- Call emulation, and circuit test and loop-line test
- PPPoE/DHCP simulation testing
- WLAN emulation

Layer 3 Features

- PPPoE/Static IP/DHCP
- NAT/NAPT
- Port forwarding
- ALG, UPnP
- DDNS/DNS server/DNS client
- IPv6/IPv4 dual stack, and DS-Lite
- Static/Default routes
- Multiple services on one WAN port

Multicast

- IGMP v2/v3 proxy /snooping
- MLD v1/v2 snooping

QoS

- Ethernet port rate limitation
- 802.1p priority
- SP/WRR/SP+WRR
- Broadcast packet rate limitation

Security

- SPI firewall
- Filtering based on
MAC/IP/URL addresses

Common O&M

- OMCI/Web UI/TR069
- Dual-system software backup and rollback

Power Saving

- Indicator power saving
- Scheduled Wi-Fi shutdown